



Combined Heat and Power (CHP) for Primary Power and HVAC in Manufacturing



Agenda

- Who is Harbec Plastics, Inc.?
- Reasons for seeking the CHP alternative.
- Problems to overcome.
- The Harbec CHP Project.
 - Microturbine choice
 - Steps to implementation
 - Components used
- What lies ahead?



Who is Harbec Plastics, Inc./?

- Established in 1977
- Located in Ontario, NY (Rochester)
- Precision Custom Injection Molder
 - Engineering Models / Quick Manufacturing Solutions (QMS[®])
 - Precision Moldmaking
 - Custom Injection Molding of typically complex component parts
 - Insert molding
 - High tolerance molding
 - Highly engineered resins
- ISO 9002, QS 9000, ISO 14001 certified
- "Technical Innovation with Environmental Responsibility"
- Proponent of sustainable manufacturing using eco-economic measures and practices.



The Reasons for seeking the CHP alternative

- High energy costs
 - #1 reason for businesses leaving New York State
 - Competing in world market means constant pursuit of cost effectiveness and competitive pricing.
- Need to improve electrical power reliability.
- Need to improve environmental control of manufacturing facility.
 - Consistent product quality year round.
- Desire to incorporate renewable energy potentials.



Problems to Overcome


- Utility related problems with Distributed Generation in New York State.
 - No Net Metering
 - Standby Tariffs
 - Utility obstacles and road-blocks
- Difficult to secure financing
 - More than 30 bank rejections
 - No existing economic models
 - Projected 7 to 10 year payback
- Difficult to find engineering partner willing to work with Microturbines.

- Microturbines were selected engine solution
 - Increased reliability
 - Decreased maintenance requirements
 - No increase in staff
 - More positive environmental impact ISO 14001
 - Lower Emissions
 - No lubricants, filters, or coolants to deal with



- Implementation requirements
 - Found IBC Engineering company
 - Developed banking solution
 - Combined CHP plant with needed warehouse expansion









- 25 CNG fueled 30kW
 Microturbines
 - 750 kW max potential
 - 500 kW Harbec's maximum load requirement
 - 250 kW redundance





- 5 Heat exchangers
 - 1 unit per four microturbines





- 1 Absorptive Chiller
 - Converts 210° water to 44°-47° water





3 - 10 hp CNG rotary Compressors





17,000' of 1"
 Diameter tubing for radiant floor heating





Computer controlled sensing and delivery system







- Addition of 250 kW wind generator to accomplish wind/microturbine hybrid.
- Anticipated joint development project with NYSERDA to research methods for improving CHP system efficiency.
- Beyond...
 - Increased utilization of thermal potential for application to manufacturing process heat requirements.
 - Implementation of Stuart Electrolyzer to store excess wind as hydrogen (hythane) for use in microturbine or future fuel cells.





Q&A

Thank You.

Bob Bechtold Harbec Plastics, Inc. 369 Route 104 Ontario, NY 14519 bxb@harbec.com www.harbec.com 1-888-521-4416 Fax 1-585-265-1306