

CHARGING EQUIPMENT MODEL
AS2P60-EVSE SINGLE

Solid State Advanced Level 2 AC Charging.

Basic Equipment Details

Type of Mount	Pedestal or wall-mounted
Number of Ports	Single
Intended Installation Setting	<ul style="list-style-type: none"> • Public • Workplace • Multi-Unit Dwelling
Networking Capability	Optional
Indicate whether the equipment uses an open standard protocol as a basic framework for purposes of network interoperability and for communication with the network services provider, and specify the protocol (such as OCPP)	OCPP
Network providers used to date	<ul style="list-style-type: none"> • Atom Power
Input Power (kW AC)	11.5 kW
Rated Output Power (kW AC)	11.5 kW
Can the equipment split power between multiple ports?	N/A
Dimensions (HxWxD, in inches)	61" x 6" x 9"
Charging cable length (in feet)	9'
Operating temperature range	-22F to 122F
Is the equipment ENERGY STAR® certified?	No
If no, do you have a Partnership Agreement with Energy Star®?	Yes
Does the equipment have a display screen?	No
Method(s) of Payment Accepted	<ul style="list-style-type: none"> • Mobile Phone App
How do customers purchase the equipment?	<ul style="list-style-type: none"> • From the Manufacturer • From the Network Providers • From 3rd Party Distributers
Warranty Duration (months)	24 months

Special Features Included in the Equipment

Atom Power's equipment executes a local energy management strategy which is not cloud dependant. Additionally, the switching takes place in the breaker (not in the wall box or pedestal). A key impact of this architecture is that there is no shock hazard in the pedestal or wall box if the equipment is struck by a vehicle or vandalized.

Optional Accessories

N/A

Optional Services

- Extended Warranty
- OTA Firmware Updates;

Distributors

Atom Power

www.atompower.com

Ryan Rizor - 828-318-5999 - rrizor@atompower.com

ESD Global LLC

www.esd-global.com

Vrindavanam Murali - 908-331-5063 - murali.vrindavanam@esd-global.com