

Ruggedized version of ClipperCreek’s popular high power HCS-60. The HCS-60R features a rubber overmolded SAE J1772 connector, a field-replaceable latch, and a 5 year warranty. The HCS-60R is an affordable solution designed for fleet, parking lot and extreme weather conditions.

Basic Equipment Details

Type of Mount	Pedestal or wall-mounted
Number of Ports	Single
Intended Installation Setting	Multi-unit dwelling
Networking Capability	Non-Networked
Indicate whether the equipment uses an open standard protocol as a basic framework for purposes of network interoperability and for communication with the network services provider, and specify the protocol (such as OCPP)	N/A
Network providers used to date	N/A
Input Power (kW AC)	11.5 kW
Rated Output Power (kW AC)	11.5 kW
Can the equipment split power between multiple ports?	N/A
Dimensions (HxWxD, in inches)	19.7” x 8.9” x 5.3”
Charging cable length (in feet)	25
Operating temperature range	(-22 to 122)
Is the equipment ENERGY STAR® certified?	Yes
Does the equipment have a display screen?	No
Method(s) of Payment Accepted	ClipperCreek HCS EVSE are compatible with third party access control, monitoring and payment collection system.
How do customers purchase the equipment?	<ul style="list-style-type: none"> • From the Manufacturer • From the Network Providers
Warranty Duration (months)	36 months

Special Features Included in the Equipment

Optional, generic load management and access control interfaces are available for this product. These interfaces provide a generic control connection for connection to existing or third party load control systems.

Optional Accessories

- PMD-10T pedestal
- PMD-10R ruggedized pedestal
- HCS 4' single pedestal
- HCS 4' dual pedestal
- Cable management extension with retractors

Optional Services

N/A

Distributors

ClipperCreek, Inc.

www.clippercreek.com

Will Barrett - 530-887-1674 x 303 - will@clippercreek.net