

The smart charging stations of the SmartTWO™ family are specially made for areas dealing with harsh climate and subject to vandalism. Their robustness, durability, and access control system bring unparalleled quality for this charging infrastructure designed for commercial and industrial use.

Basic Equipment Details

Type of Mount	Both pedestal or wall-mounted available
Number of Ports	Single
Intended Installation Setting	<ul style="list-style-type: none"> • Public • Workplace • Multi-Unit Dwelling
Networking Capability	Networked
Indicate whether the equipment uses an open standard protocol as a basic framework for purposes of network interoperability and for communication with the network services provider, and specify the protocol (such as OCPP)	No
Network providers used to date	FLO Network
Input Power (kW AC)	6.2 kW (208V) 7.2 kW (240V)
Rated Output Power (kW AC)	6.2 kW (208V) 7.2 kW (240V)
Can the equipment split power between multiple ports?	No
Dimensions (HxWxD, in inches)	Wall-mounted: 8.125" x 55" x 9.75" Pedestal: 9.75" x 8.25" x 82"
Charging cable length (in feet)	25
Operating temperature range	-40°F to 122°F
Is the equipment ENERGY STAR® certified?	No
Does the equipment have a display screen?	Yes - LED
Method(s) of Payment Accepted	<ul style="list-style-type: none"> • Credit Card (by phone) • Network RFID Tag • Mobile Phone App
How do customers purchase the equipment?	<ul style="list-style-type: none"> • From the Manufacturer • From Network Providers • From Third Party Distributors
Warranty Duration (months)	24 months

Special Features Included in the Equipment

- All SmartTWO stations come with easily customizable branding

Optional Accessories

- Patented locking door to protect connector (standard)

Optional Services

- Extended warranty
- Technical support
- Maintenance service

Distributors

FLO Services

www.flo.com

Brookes Shean | 416-427-3339 | bshean@flo.com