

Single Port up to 19.2 kW output and software selectable.

**Basic Equipment Details**

Type of Mount	Pedestal or wall-mount available
Number of Ports	Single
Intended Installation Setting	<ul style="list-style-type: none"> <li>• Public</li> <li>• Workplace</li> <li>• Multi-Unit Dwelling</li> </ul>
Networking Capability	Optional
Indicate whether the equipment uses an open standard protocol as a basic framework for purposes of network interoperability and for communication with the network services provider, and specify the protocol (such as OCPP)	Rapi, Ocpp
Network providers used to date	EvGateway
Input Power (kW AC)	0-19.2 kW software selectable
Rated Output Power (kW AC)	19.2 kW
Can the equipment split power between multiple ports?	Yes, built-in
Dimensions (HxWxD, in inches)	12x7x6
Charging cable length (in feet)	25
Operating temperature range	-31 to +150 F
Is the equipment ENERGY STAR® certified?	Yes
Does the equipment have a display screen?	Yes - LCD
Method(s) of Payment Accepted	<ul style="list-style-type: none"> <li>• Credit Card</li> <li>• Network provider dependent</li> </ul>
How do customers purchase the equipment?	From the Manufacturer
Warranty Duration (months)	39 Months

---

## Special Features Included in the Equipment

- Made of 316 “Marine Grade” SS

---

## Optional Accessories

- Cable management system
- Mirror/satin doors
- Coiled or straight J1772 cords
- Keylocks
- Custom mounting systems
- High security mounting system

## Optional Services

- Free tech support

---

## Distributor

**LiquidSky Technologies, Inc.**

**[www.WattZilla.com](http://www.WattZilla.com)**

Frank Gangi | 857-389-9893 | [info@wattzilla.com](mailto:info@wattzilla.com)