

Standard model, manual cable management, SAE J1772, 208-240VAC, 30A, 7.2 KW, Zigbee short range wireless or serial cable connections to cellular or ethernet paystation.

Basic Equipment Details

Type of Mount	Both pedestal or wall-mounted available
Number of Ports	Single
Intended Installation Setting	<ul style="list-style-type: none"> • Public • Workplace • Multi-Unit Dwelling
Networking Capability	Optional
Indicate whether the equipment uses an open standard protocol as a basic framework for purposes of network interoperability and for communication with the network services provider, and specify the protocol (such as OCPP)	Yes OCPP
Network providers used to date	<ul style="list-style-type: none"> • Livingston EV Network • Greenlots
Input Power (kW AC)	(240VAC, 30A) 7.2
Rated Output Power (kW AC)	7.2 KW
Can the equipment split power between multiple ports?	N/A
Dimensions (HxWxD, in inches)	37.00x10.50x10.50
Charging cable length (in feet)	20
Operating temperature range	-22 to 122
Is the equipment ENERGY STAR® certified?	No
If no, do you have a Partnership Agreement with Energy Star?	Yes
Does the equipment have a display screen?	No
Method(s) of Payment Accepted	<ul style="list-style-type: none"> • Credit Card (by phone) • Network RFID Tag • Mobile Phone App
How do customers purchase the equipment?	<ul style="list-style-type: none"> • From the Manufacturer • From Network provider(s)
Warranty Duration (months)	36 Months

Special Features Included in the Equipment

- Cable management & canopy

Optional Accessories

- Cable management
- QR code access
- LED area security light
- Canopy

Optional Services

- Turnkey planning & installation
- Remote & on-site tech support
- Operation & network services
- Extended warranty & maintenance
- Data collection & integration
- Financing available

Distributors

Livingston Energy Group

www.solution.energy

Schuyler Poukish | 844-623-1001 ext. 1 | schuyler@solution.energy