

Single port (J17172) Level 2 charging station capable of multiple configurations including an OCPP Network solution. The station can be individually wall mounted or up to two (2) units mounted to our universal pedestal solution.

Basic Equipment Details

Type of Mount	Both pedestal or wall-mounted available
Number of Ports	Single
Intended Installation Setting	<ul style="list-style-type: none"> • Public • Workplace • Multi-Unit Dwelling
Networking Capability	Networked
Indicate whether the equipment uses an open standard protocol as a basic framework for purposes of network interoperability and for communication with the network services provider, and specify the protocol (such as OCPP)	Yes, OCPP version 1.6J
Network providers used to date	Greenlots
Input Power (kW AC)	7.68kW
Rated Output Power (kW AC)	7.68kW
Can the equipment split power between multiple ports?	N/A
Dimensions (HxWxD, in inches)	11.14" x 7.56" x 3.11"
Charging cable length (in feet)	25
Operating temperature range	(-22 to 122)
Is the equipment ENERGY STAR® certified?	Yes
Does the equipment have a display screen?	Yes - LED
Method(s) of Payment Accepted	<ul style="list-style-type: none"> • Network RFID Tag • Mobile Phone App • Toll Free Phone Number
How do customers purchase the equipment?	<ul style="list-style-type: none"> • From the Manufacturer
Warranty Duration (months)	48 Months

Special Features Included in the Equipment

- Custom label branding available
- Static and dynamic power sharing capabilities
- NEMA 4 enclosure

Optional Accessories

- Aluminum pedestal that will support 1 or 2 units
- Can be integrated into solar/canopy systems
- RFID key fob authentication.

Optional Services

- Extended warranty available
- Network set-up and monitoring
- Toll-free driver support
- Installation project management
- Driver app listing
- Non-network usage reporting option

Distributors

NovaCHARGE, LLC
www.novacharge.net

Jody McDevitt | 866-296-2437 | jody@novacharge.net