

Robust Commercial Charging Station designed to withstand outdoor applications. Our 30 amp version will provide about 20 miles of range per hour of charging..

**Basic Equipment Details**

Type of Mount	Pedestal or wall-mount available
Number of Ports	Dual
Intended Installation Setting	Multi-Unit Dwelling
Networking Capability	Non-Networked
Indicate whether the equipment uses an open standard protocol as a basic framework for purposes of network interoperability and for communication with the network services provider, and specify the protocol (such as OCPP)	N/A
Network providers used to date	N/A
Input Power (kW AC)	7.2 kW
Rated Output Power (kW AC)	7.2 kW
Can the equipment split power between multiple ports?	No
Dimensions (HxWxD, in inches)	56.25x20x10
Charging cable length (in feet)	18
Operating temperature range	-22F to 131F
Is the equipment ENERGY STAR® certified?	No
Does the equipment have a display screen?	No
Method(s) of Payment Accepted	N/A
How do customers purchase the equipment?	<ul style="list-style-type: none"> <li>• From the Manufacturer</li> <li>• From Third Party Distributors</li> </ul>
Warranty Duration (months)	24 Months

---

## Special Features Included in the Equipment

- Available in 16a, 30a, 40a & 70a output

---

## Optional Accessories

- Parking space signage
- Cable retractors
- EVSE protector (for wall mount units)
- Custom vinyl graphics
- Stand-alone data collection/reporting
- EVSE mounting base (for pedestal units)

## Optional Services

- Extended warranties

---

## Distributors

### PowerCharge

[www.PowerChargeEV.com](http://www.PowerChargeEV.com)

Mike Moser | 585-533-4085 | [mike@PowerChargeEV.com](mailto:mike@PowerChargeEV.com)

### EV Charge Solutions

[www.evCHARGEolutions.com](http://www.evCHARGEolutions.com)

Wendy Quinn | 585-533-4051 | [wquinn@evCHARGEolutions.com](mailto:wquinn@evCHARGEolutions.com)