

CHARGING EQUIPMENT MODEL

PRO-LINK (P20DPN-RC PEDESTAL) (P20DWN-RC WALL)

PowerCharge
www.PowerChargeEV.com

Robust Commercial Charging Station designed to withstand outdoor applications. Our 30 amp version will provide about 20 miles of range per hour of charging.

Basic Equipment Details

Type of Mount	Pedestal or wall-mount available
Number of Ports	Dual
Intended Installation Setting	<ul style="list-style-type: none">• Public• Workplace• Multi-Unit Dwelling
Networking Capability	Networked
Indicate whether the equipment uses an open standard protocol as a basic framework for purposes of network interoperability and for communication with the network services provider, and specify the protocol (such as OCPP)	OCPP
Network providers used to date	<ul style="list-style-type: none">• EV Connect• Greenlots
Input Power (kW AC)	7.2 kW
Rated Output Power (kW AC)	7.2 kW
Can the equipment split power between multiple ports?	No
Dimensions (HxWxD, in inches)	56.25x20x10
Charging cable length (in feet)	18
Operating temperature range	-22F to 131F
Is the equipment ENERGY STAR® certified?	No
Does the equipment have a display screen?	Yes
Method(s) of Payment Accepted	<ul style="list-style-type: none">• Credit Card• Network RFID Tag• Mobile Phone App
How do customers purchase the equipment?	<ul style="list-style-type: none">• From the Manufacturer• From Third Party Distributors
Warranty Duration (months)	24 Months

Special Features Included in the Equipment

- Available in 16a, 30a, 40a & 70a output

Optional Accessories

- Parking space signage
- Cable retractors
- EVSE protector (for wall mount units)
- Custom vinyl graphics
- Stand-alone data collection/reporting
- EVSE mounting base (for pedestal units)

Optional Services

- Extended warranties

Distributors

PowerCharge

www.PowerChargeEV.com

Mike Moser | 585-533-4085 | mike@PowerChargeEV.com

EV Charge Solutions

www.evCHARGEolutions.com

Wendy Quinn | 585-533-4051 | wquinn@evCHARGEolutions.com