

CHARGING EQUIPMENT MODEL
PLATINUM (#E20DPP)

PowerCharge
 www.PowerChargeEV.com

Networked version with OCPP 1.6, RFID reader, two-line display, LTE Cellular modem, and WiFi Connectivity.

Basic Equipment Details

Type of Mount	Pedestal-mount available
Number of Ports	Dual
Intended Installation Setting	<ul style="list-style-type: none"> • Public • Workplace • Multi-Unit Dwelling
Networking Capability	Networked
Indicate whether the equipment uses an open standard protocol as a basic framework for purposes of network interoperability and for communication with the network services provider, and specify the protocol (such as OCPP)	Yes, OCPP 1.6
Network providers used to date	<ul style="list-style-type: none"> • EV Connect • Greenlots
Input Power (kW AC)	7.6 kW
Rated Output Power (kW AC)	7.6 kW (adjustable to 3.8 or 5.8 kW)
Can the equipment split power between multiple ports?	No
Dimensions (HxWxD, in inches)	11.14x7.56x3.11
Charging cable length (in feet)	25
Operating temperature range	-22F to 131F
Is the equipment ENERGY STAR® certified?	No
Does the equipment have a display screen?	Yes
Method(s) of Payment Accepted	<ul style="list-style-type: none"> • Credit Card • Network RFID Tag • Mobile Phone App
How do customers purchase the equipment?	<ul style="list-style-type: none"> • From the Manufacturer • From Third Party Distributors
Warranty Duration (months)	36 Months

Special Features Included in the Equipment

- Adjustable amperage (16, 24, 32)

Optional Accessories

- Parking space signage
- Cable Retractors
- EVSE protector (for wall mount units)
- Custom vinyl graphics
- Stand-alone data collection/reporting
- EVSE mounting base (for pedestal units)

Optional Services

- Extended warranties

Distributors

PowerCharge

www.PowerChargeEV.com

Mike Moser | 585-533-4085 | mike@PowerChargeEV.com

EV Charge Solutions

www.evCHARGEolutions.com

Wendy Quinn | 585-533-4051 | wquinn@evCHARGEolutions.com